

SPECIALTY CARTRIDGES



RESIN & MEDIA CARTRIDGES

We loaded our most popular resins into handy disposable cartridges to fit most industry standard plastic filter housings. All cartridges feature the SWT ProSoft™, ProSelect™, and ProActive™ media lines, and have a 20-micron polypropylene filter pad

for prefiltration. All carbon is water or acid pre-washed to remove carbon fines. These cartridges are quickly becoming the professional choice in water filtration. SWT's Specialty Cartridges are more affordable than ever.

| Part Number | Description | Nominal Size Inches | Capacity | Flow Rate | | Case Qty. | Case Wt. Lbs. |
|-------------|-------------|---------------------|----------|---------------|-------------|-----------|---------------|
| | | | | Operating GPM | Maximum GPM | | |

ProActive™ Acid Washed Coal Based Carbon Cartridges — Chlorine & VOC Removal

| | | | | | | | |
|---------|------------------------------|----------|-------------|------|------|-----|----|
| ER66005 | 20 x 50 Acid Washed Coal GAC | 2.5 x 10 | 4,000 gal. | 0.75 | 1.0 | 12* | 15 |
| ER76005 | 20 x 50 Acid Washed Coal GAC | 2.5 x 20 | 6,300 gal. | 1.00 | 2.00 | 9* | 21 |
| ER86005 | 12 x 40 Acid Washed Coal GAC | 4.5 x 10 | 7,750 gal. | 2.00 | 4.00 | 8* | 20 |
| ER96005 | 12 x 40 Acid Washed Coal GAC | 4.5 x 20 | 17,000 gal. | 3.00 | 5.00 | 4* | 21 |

ProActive™ Acid Washed Coconut Shell Carbon Cartridges — Chlorine & Organics Removal

| | | | | | | | |
|---------|---------------------------------|----------|-------------|------|------|-----|----|
| ER66006 | 20 x 50 Acid Washed Coconut GAC | 2.5 x 10 | 4,000 gal. | 0.75 | 1.0 | 12* | 15 |
| ER76006 | 20 x 50 Acid Washed Coconut GAC | 2.5 x 20 | 9,000 gal. | 1.00 | 2.00 | 9* | 21 |
| ER86006 | 12 x 40 Acid Washed Coconut GAC | 4.5 x 10 | 13,000 gal. | 2.00 | 4.00 | 8* | 20 |
| ER96006 | 12 x 40 Acid Washed Coconut GAC | 4.5 x 20 | 30,000 gal. | 3.00 | 5.00 | 4* | 21 |

ProActive™ Centaur Catalytic Carbon Cartridges — Chloramine & Hydrogen Sulfide Removal

| | | | | | | | |
|---------|-------------------------------|----------|-------------|------|------|-----|----|
| ER66007 | 20 x 50 Centaur Catalytic GAC | 2.5 x 10 | 4,000 gal. | 0.75 | 1.0 | 12* | 18 |
| ER76007 | 20 x 50 Centaur Catalytic GAC | 2.5 x 20 | 6,300 gal. | 1.00 | 2.00 | 9* | 25 |
| ER86007 | 12 x 40 Centaur Catalytic GAC | 4.5 x 10 | 7,700 gal. | 2.00 | 4.00 | 8* | 24 |
| ER96007 | 12 x 40 Centaur Catalytic GAC | 4.5 x 20 | 17,000 gal. | 3.00 | 5.00 | 4* | 25 |

High Purity Mixed Bed Deionization Resin Cartridges — TDS Removal

| | | | | | | | |
|---------|------------------------------|----------|-----------|------|------|-----|----|
| ER68100 | Mixed Bed Deionization Resin | 2.5 x 10 | 450 gr. | 0.2 | 0.3 | 12* | 42 |
| ER78100 | Mixed Bed Deionization Resin | 2.5 x 20 | 900 gr. | 0.20 | 0.60 | 9* | 32 |
| ER88100 | Mixed Bed Deionization Resin | 4.5 x 10 | 1,050 gr. | 0.50 | 0.80 | 8* | 29 |
| ER98100 | Mixed Bed Deionization Resin | 4.5 x 20 | 2,350 gr. | 0.50 | 1.50 | 4 | 32 |

Color Changing High Purity Demineralization Resin Cartridges — TDS Removal

| | | | | | | | |
|-------------|---------------------------------|----------|---------|-----|-----|-----|----|
| ER68100C-CC | Self Indication Mixed Bed Resin | 2.5 x 10 | 450 gr. | 0.2 | 0.3 | 12* | 42 |
|-------------|---------------------------------|----------|---------|-----|-----|-----|----|

ProSoft™ Gold Cation Resin Cartridges — Hardness & Iron Removal

| | | | | | | | |
|---------|---------------------------------|----------|-----------|------|------|-----|----|
| ER68200 | Softening Resin, NSF/ANSI 44/61 | 2.5 x 10 | 1,113 gr. | 0.05 | 0.27 | 12* | 42 |
| ER78200 | Softening Resin, NSF/ANSI 44/61 | 2.5 x 20 | 2,520 gr. | 0.12 | 0.60 | 8* | 32 |
| ER88200 | Softening Resin, NSF/ANSI 44/61 | 4.5 x 10 | 2,818 gr. | 0.13 | 0.67 | 8* | 32 |
| ER98200 | Softening Resin, NSF/ANSI 44/61 | 4.5 x 20 | 6,237 gr. | 0.30 | 1.49 | 4* | 37 |

* Sold in case quantities only.

SPECIALTY CARTRIDGES



RESIN & MEDIA CARTRIDGES

| Part Number | Description | Nominal Size Inches | Capacity | Flow Rate | | Case Qty. | Case Wt. Lbs. |
|-------------|-------------|---------------------|----------|---------------|-------------|-----------|---------------|
| | | | | Operating GPM | Maximum GPM | | |

MetalEase-AS+5™ Cartridges — Arsenic (As⁺⁵) Removal

| | | | | | | | |
|----------------|------------------------------------|----------|-------------|------|------|----|----|
| METAL-AS5-10 | Arsenic Removal Media, NSF/ANSI 61 | 2.5 x 10 | 5,936 gal. | 0.10 | 0.40 | 12 | 44 |
| METAL-AS5-20 | Arsenic Removal Media, NSF/ANSI 61 | 2.5 x 20 | 13,440 gal. | 0.22 | 0.90 | 9* | 34 |
| METAL-AS5-10BB | Arsenic Removal Media, NSF/ANSI 61 | 4.5 x 10 | 15,030 gal. | 0.25 | 1.00 | 8* | 31 |
| METAL-AS5-20BB | Arsenic Removal Media, NSF/ANSI 61 | 4.5 x 20 | 33,264 gal. | 0.56 | 2.22 | 4* | 34 |

Fluoride Removal Cartridges

| | | | | | | | |
|--------------|-----------------------------------|----------|------------|------|------|----|----|
| METAL-ALF-10 | MetalEase-ALF™ Media, NSF/ANSI 61 | 2.5 x 10 | 2,406 ppm | 0.03 | 0.06 | 12 | 40 |
| ER78400 | Fluoride Removal Media | 2.5 x 20 | 5,448 ppm | 0.06 | 0.12 | 9* | 35 |
| ER88400 | Fluoride Removal Media | 4.5 x 10 | 6,093 ppm | 0.07 | 0.13 | 8* | 30 |
| ER98400 | Fluoride Removal Media | 4.5 x 20 | 13,484 ppm | 0.15 | 0.30 | 4* | 34 |

ProSelect™ Tannin Resin Cartridges — Organics & Tannins Removal

| | | | | | | | |
|---------|-------------------------------------|----------|----------|------|------|-----|----|
| ER68500 | Tannin Selective Resin, NSF/ANSI 61 | 2.5 x 10 | 119 gal. | 0.05 | 0.11 | 12* | 42 |
| ER78500 | Tannin Selective Resin, NSF/ANSI 61 | 2.5 x 20 | 269 gal. | 0.12 | 0.24 | 8* | 32 |
| ER88500 | Tannin Selective Resin, NSF/ANSI 61 | 4.5 x 10 | 300 gal. | 0.13 | 0.27 | 8* | 32 |
| ER98500 | Tannin Selective Resin, NSF/ANSI 61 | 4.5 x 20 | 665 gal. | 0.30 | 0.59 | 4* | 37 |

ProSelect™ Nitrate Resin Cartridges — Nitrate Removal

| | | | | | | | |
|---------|--------------------------------------|----------|-----------|------|------|-----|----|
| ER68300 | Nitrate Selective Resin, NSF/ANSI 61 | 2.5 x 10 | 334 gr. | 0.05 | 0.21 | 12* | 42 |
| ER78300 | Nitrate Selective Resin, NSF/ANSI 61 | 2.5 x 20 | 756 gr. | 0.12 | 0.48 | 9* | 31 |
| ER88300 | Nitrate Selective Resin, NSF/ANSI 61 | 4.5 x 10 | 845 gr. | 0.13 | 0.54 | 8* | 27 |
| ER98300 | Nitrate Selective Resin, NSF/ANSI 61 | 4.5 x 20 | 1,871 gr. | 0.30 | 1.19 | 4* | 31 |

* Sold in case quantities only.