

INDUSTRIAL CARBON FILTERS



ACTIVATED CARBON FILTRATION SYSTEMS WITH COMPOSITE TANKS

SWT Carbon Filters with COMPOSITE TANKS, Aquamatic Diaphragm Valves, Time Initiated Backwash

Part Number	Flow Rate VOC Red. GPM (LPM)	Flow Rate Standard GPM (LPM)	Flow Rate Peak GPM (LPM)	Flow Rate @ 5 PSI Drop GPM (LPM)	Media Quantity Cu. Ft. (Liters)	Bed Surface Area Sq. Ft.	Backwash Rate GPM (LPM)	Tank Size Inches	Diaphragm Valve Size
CCC15P-2472	< 20 (76)	35 (132)	48 (182)	25 (95)	10 (283)	3.1	42 (159)	24 x 72	1.5" Composite
CCC20P-2472	< 20 (76)	35 (132)	48 (182)	25 (95)	10 (283)	3.1	42 (159)	24 x 72	2" Composite
CCC15C-3072	< 32 (121)	56 (212)	75 (284)	40 (151)	16 (453)	4.9	70 (265)	30 x 72	1.5" Cast Iron
CCC15P-3072	< 32 (121)	56 (212)	75 (284)	40 (151)	16 (453)	4.9	70 (265)	30 x 72	1.5" Composite
CCC20C-3072	< 32 (121)	56 (212)	75 (284)	40 (151)	16 (453)	4.9	70 (265)	30 x 72	2" Cast Iron
CCC20P-3072	< 32 (121)	56 (212)	75 (284)	40 (151)	16 (453)	4.9	70 (265)	30 x 72	2" Composite
CCC20C-3672	< 40 (151)	70 (265)	105 (397)	55 (208)	20 (566)	7.0	95 (360)	36 x 72	2" Cast Iron
CCC20P-3672	< 40 (151)	70 (265)	105 (397)	55 (208)	20 (566)	7.0	95 (360)	36 x 72	2" Composite
CCC25C-3672	< 40 (151)	70 (265)	105 (397)	55 (208)	20 (566)	7.0	95 (360)	36 x 72	2.5" Cast Iron
CCC30C-3672	< 40 (151)	70 (265)	105 (397)	55 (208)	20 (566)	7.0	95 (360)	36 x 72	3" Cast Iron
CCC30P-3672	< 40 (151)	70 (265)	105 (397)	55 (208)	20 (566)	7.0	95 (360)	36 x 72	3" Composite
CCC20P-4272	< 50 (189)	85 (322)	144 (545)	75 (284)	25 (708)	9.6	135 (511)	42 x 72	2" Composite
CCC25C-4272	< 50 (189)	85 (322)	144 (545)	75 (284)	25 (708)	9.6	135 (511)	42 x 72	2.5" Cast Iron
CCC30C-4272	< 50 (189)	85 (322)	144 (545)	75 (284)	25 (708)	9.6	135 (511)	42 x 72	3" Cast Iron
CCC30P-4272	< 50 (189)	85 (322)	144 (545)	75 (284)	25 (708)	9.6	135 (511)	42 x 72	3" Composite
CCC20P-4872	< 72 (273)	125 (473)	180 (681)	100 (379)	36 (1019)	12.6	170 (644)	48 x 72	2" Composite
CCC25C-4872	< 72 (273)	125 (473)	200 (757)	100 (379)	36 (1019)	12.6	170 (644)	48 x 72	2.5" Cast Iron
CCC30C-4872	< 72 (273)	125 (473)	200 (757)	100 (379)	36 (1019)	12.6	170 (644)	48 x 72	3" Cast Iron
CCC30P-4872	< 72 (273)	125 (473)	200 (757)	100 (379)	36 (1019)	12.6	170 (644)	48 x 72	3" Composite
CCC30C-6367	< 90 (341)	155 (587)	300 (1136)	150 (568)	45 (1274)	19.6	275 (1041)	63 x 67	3" Cast Iron
CCC30P-6367	< 90 (341)	155 (587)	300 (1136)	150 (568)	45 (1274)	19.6	275 (1041)	63 x 67	3" Composite
CCC40C-6367	< 90 (341)	155 (587)	300 (1136)	150 (568)	45 (1274)	19.6	275 (1041)	63 x 67	4" Cast Iron
CCC30C-6386	< 110 (416)	200 (757)	330 (1249)	190 (719)	55 (1557)	23.8	330 (1249)	63 x 86	3" Cast Iron
CCC30P-6386	< 110 (416)	200 (757)	330 (1249)	190 (719)	55 (1557)	23.8	330 (1249)	63 x 86	3" Composite
CCC40C-6386	< 110 (416)	200 (757)	330 (1249)	190 (719)	55 (1557)	23.8	330 (1249)	63 x 86	4" Cast Iron

INDUSTRIAL CARBON FILTERS



ACTIVATED CARBON FILTRATION SYSTEMS WITH COMPOSITE TANKS

System is unassembled (for shipping purposes) and includes all necessary valves, tank, grades of media, underbedding, internal distributors/strainers, drain line flow controls, and the clock/timer/stager assembly mounted into a control box. External piping is not included. Customer may want to consider system additions of pressure gauges, sample cocks, vacuum breakers, flex connectors, bypass valves, shut-offs, etc.

Cast Iron Valve available connections: (FPT: 1.5 inch, 2 inch, 2.5 inch, 3 inch); (Flanged: 3 inch, 4 inch, 6 inch)

Plastic Valve available connections: (MPT: 1.5 inch); (Male Spigot Weld: 1.5 inch, 2 inch); (Female Socket Weld: 2 inch); (Flanged: 2 inch, 3 inch)

Recommended Service Flow Rates/Ranges are based on the cu.ft. of the tank/filter bed. Slower flow rate per cu.ft. = Better Filtration

- 0.8 gpm/cu.ft. is recommended for waste water cleanup (8 to 10 minutes contact time).
- 1.5 to 2 gpm/cu.ft. = Superior filtration and minor VOC levels with less than 2 psi pressure drop
- 3.5 to 5 gpm/cu.ft. = Commercial/residential de-chlorination, taste & odor control with less than 5 psi pressure drop
- 5 to 10 gpm/cu.ft. = Sporadic peak flow rates for non-critical light commercial and residential clean water de-chlorination, taste & odor control. Peak flow rates are more a function of the valving/bed psi loss and not a recommendation of the carbon's ability to perform at these rates.

System Flow Rates as listed are based on pressure drop curves of less than 2 psi drop through the service valves.

Backwash Rates for proper bed cleaning are best achieved at 14 gpm/sq.ft. However, water temperature variation may require backwash rate adjustment. Also allow service flow and backwash variations for valve sizes, pipe sizes, pump sizes, water availability, and unique applications.

Backwash Rates allow 40% bed expansion at 60°F.

Backwash Flow Restrictors are included and can be provided to accommodate any desired backwash flow rates.

Valve Sizes and Tank Size Pairings for special flow rates and backwash rates may be substituted at customer request or are application dependent. SWT GAC carbon filters use 8 x 30 mesh bituminous coal based granular activated carbon. Acid washed carbons and coconut shell carbons are available on request. 12 x 40 or 20 x 50 mesh carbons also available.

Operating Pressure: 150 psi (10 bar)

Maximum Temperature: 140°F (60°C)

SAFE WATER TECHNOLOGIES, INC.
996 BLUFF CITY BOULEVARD, ELGIN, IL 60120 USA
TELEPHONE 847 888 6900 • FACSIMILE 847 888 6924
E MAIL: info@swtwater.com • WEB SITE: www.swtwater.com



FORM 1274
EFFECTIVE
MARCH 2004