

# ULTRAVIOLET SYSTEMS



## BETTERLIFE ULTIMA™ SYSTEM 3 SOFTENING RESIN AND CARBON WITH UV STERILIZATION



Safe Water Technologies' patented BetterLife Ultima™ system is the flagship of the SWT product line. There is no other water treatment system available for the whole house that compares. A computerized controller meters the water flow for optimal cost savings. A precise blend of ProSoft™ cation resin and ProActive™ granular activated carbon is designed to remove calcium and magnesium (hardness), chlorine, taste, odor, and many other cations and chemical contaminants from the water stream. The ultraviolet design adds bacteriological safeguards to your water supply. The final stage has an advanced polymer, one micron sediment trap, capable of removing 99.98% of Cryptosporidium and Giardia Cysts from the water stream.

### BetterLife Ultima™ System 3 Includes:

- ProSoft™ Premium cation exchange resin
- ProActive™ GAC carbon system
- 10 GPM stainless steel ultraviolet chamber
- 30,000 µw sec/cm<sup>2</sup> UV dosage
- 20 inch Big Blue® housing with 1 micron giardia filter
- Computer controlled and metered valve
- Chlorastick™ pipe sanitizing kit
- Corrosion-free system

### BetterLife Ultima™ System 3 with UV Sterilization

Part Number	Tank Size Inches	Softening Capacity		Service Flow Rate			Backwash 50% Exp. @ 50°F	Standard Connection Size*
		10 lbs. Salt/Regen.	15 lbs. Salt/Regen.	Chlorine, Taste & Odor	VOC Reduction	Peak		
BL3L-175	12 x 48	29,000 gr.	33,000 gr.	5 gpm	2 gpm	10 gpm	2.5 gpm	¾" Copper Swet

### High Sediment & Rural Applications (System Includes Option BLS-R: 10 Micron Pre-filter & 20 inch Clear Housing)

BL3L-175R	12 x 48	29,000 gr.	33,000 gr.	5 gpm	2 gpm	10 gpm	2.5 gpm	¾" Copper Swet
-----------	---------	------------	------------	-------	-------	--------	---------	----------------

International voltages available at additional cost.

\* 1 inch connections and threaded adapters available on request.

### Options

Part Number	Description
BLS-R	10 Micron Pleated Pre-filter with 20 inch Clear, Bypass Housing <b>(Highly Recommended For Rural Applications)</b>
BLS-E	Instant Start Electronic Ballast (Auto-detects 50/60 Hz)
BLS-A	Controller Board with Lamp Status LED, Audible Alarm, and Solenoid Valve Hook-up
BLS-S	Solenoid Valve Assembly — Requires Upgraded Electronic Ballast

Other media and resin combinations are available. Call for details..

**WARNING AND DISCLAIMER:** Ultraviolet treatment, chlorinating, or any other form of sanitation of contaminated water, are never 100% guaranteed for bacteriological-free water, but are EPA approved methods of water sanitation which add greatly to protection against waterborne pathogens. Proper ultraviolet sterilization is an instantaneous process which destroys 99.97% of pathogens and leaves no UV residual in the water. Periodic monitoring of the water supply and of the downstream piping system sanitation is recommended to help guard against downstream contamination or accidentally contaminated water bypass. Ultraviolet sterilization and/or chlorine, is **not recommended and should not be used** for cyst treatment.

Big Blue® is a registered trademark of Ametek, Inc.

SAFE WATER TECHNOLOGIES, INC.  
996 BLUFF CITY BOULEVARD, ELGIN, IL 60120 USA  
TELEPHONE 847 888 6900 • FACSIMILE 847 888 6924  
E MAIL: info@swtwater.com • WEB SITE: www.swtwater.com



FORM 1175  
EFFECTIVE  
FEBRUARY 2011

# ULTRAVIOLET SYSTEMS



## BETTERLIFE ULTIMA™ SYSTEM 3 SOFTENING RESIN AND CARBON WITH UV STERILIZATION

### Replacement Parts

Part Number	Description
IL10001	Ultraviolet Lamp
CF73210	10 Micron Pleated Sediment Cartridge (2.5 x 20 inch Pre-filter)
AH-PPBB201	1 Micron Absolute Pleated Cartridge for Cryptosporidium and Giardia Cysts (4.5 x 20 inch Post-filter)
APS-CSRA	Replacement Chlorastick™ Pipe Sanitizing Module
IT50003	ProActive™ Carbon (20 x 50 Mesh)
IL30001	Quartz Sleeve
UL-118RS	Red Silicone O-Ring for Quartz Sleeve
EC-LL68	Safety Spring
MA-15515343	Granular Activated Carbon Cartridge for Big Blue Housing (4.5 x 20 inch)



#### Chlorastick™ Pipe Sanitizing Kit (Included)

Contains:

- Lever Action, Brass Ball Valves
- Quick Release, Union Fittings with O-Ring Seals
- Disposable Chlorine Chamber
- Sch 80 PVC Replacement Pipe



#### Pre-filter Assembly (Optional)

Contains:

- 20 inch Clear Housing with Built-in Bypass and 0.75 inch NPT
- 2.5 x 20 inch Pleated Cartridge with 10 Micron Filtration
- Spanner Wrench
- Wall Mount Bracket



#### Post-filter Assembly (Optional)

Contains:

- 20 inch Big Blue Sump with Pressure Relief and 0.75 inch NPT
- 4.5 x 20 inch Pleated Cartridge with 1 Micron Filtration for Giardia Cysts
- Spanner Wrench
- Wall Mount Bracket

### Additional Specifications — BetterLife Ultima™ System 3

Shipping Dimensions (Inches):

**BL3L-175:** 17 x 13 x 58 @ 130 lbs. / Brine Tank: 18 x 16 x 37 @ 35 lbs.

Operating Pressure: 20 to 125 PSI

Operating Temperature: 36 to 120°F (2 to 48.9°C)