

# FLOW CONTROLS



## STAINLESS STEEL FLOW CONTROLS



1.25 inch Stainless Steel Flow Control



1.5 inch Stainless Steel Flow Control



2 inch Stainless Steel Flow Control



3 inch Stainless Steel Flow Control

Operating Pressures: 20 PSI Minimum / 125 PSI Maximum (1.4 to 8.6 bar)

Operating Temperatures: 40°F Minimum / 110°F Maximum (4° to 43° C)

NOTE: These drain line flow controls should not be used as the primary flow control device for critical or health effect applications.

### Stainless Steel Flow Controls

Part Number	Inlet		Outlet		Flow Rate Range	
	Size Inches	Type	Size Inches	Type	GPM	LPM
LC-FC125M15F(FR)-SS *	1.25	Male NPT	1.5	Female NPT	9 to 85	34.0 to 321.7
LC-FC125M15FB(FR)-SS *	1.25	Male NPT	1.5	Female BSPT	9 to 85	34.0 to 321.7
LC-FC15M15F(FR)-SS *	1.5	Male NPT	1.5	Female NPT	9 to 85	34.0 to 321.7
LC-FC15M15FB(FR)-SS *	1.5	Male NPT	1.5	Female BSPT	9 to 85	34.0 to 321.7
LC-FC2M2F(FR)-SS *	2.0	Male NPT	2.0	Female NPT	0.7 to 150	2.64 to 567.8
LC-FC2MB2F(FR)-SS *	2.0	Male BSPT	2.0	Female NPT	0.7 to 150	2.64 to 567.8
LC-FC2M2FB(FR)-SS *	2.0	Male NPT	2.0	Female BSPT	0.7 to 150	2.64 to 567.8
LC-FC2MB2FB(FR)-SS *	2.0	Male BSPT	2.0	Female BSPT	0.7 to 150	2.64 to 567.8
LC-FC3M3F(FR)-SS *	3.0	Male NPT	3.0	Female NPT	9 to 225	34.0 to 851.7
LC-FC3MB3F(FR)-SS *	3.0	Male BSPT	3.0	Female NPT	9 to 225	34.0 to 851.7
LC-FC3M3FB(FR)-SS *	3.0	Male NPT	3.0	Female BSPT	9 to 225	34.0 to 851.7
LC-FC3MB3FB(FR)-SS *	3.0	Male BSPT	3.0	Female BSPT	9 to 225	34.0 to 851.7

\* (FR) denotes Flow Rate in gallons per minute (GPM).

Example: LC-FC2M2F33-SS is a Stainless Steel Flow Control with 2 inch male NPT input, 2 inch female NPT output, and 33 GPM flow rate.