

# DEIONIZERS



## iEx™ COMMERCIAL D.I. SYSTEMS

*Safe Water Technologies begins development of new product line.*

### **iEx™ D.I. Systems** now available from SWT.



New top mounted valving and new GE controls make deionized water production easy and cost effective. These two column (one cation and one anion in series) systems are now available in five introductory flow rates and capacities, and include a monitoring system and sequential regeneration.

#### Applications

- TDS Reduction
- Carwashes
- Boiler Feed
- Cooling Towers
- Process Water
- Silica Reduction\*
- Laboratory
- Plating and Chemical

\* Contact SWT for details.

#### Accessories

- Neutralization Stations and Tanks
- Low Flow Recirculation Loop
- Deluxe Monitoring System with Audible Alarm
- Drum Heater
- Regeneration Chemical Float

#### iEx™ Commercial D.I. Systems Specifications

Tank Size Inches	Pipe Size Inches	Service Flow GPM	System Capacity**
18 x 65	1.5	10 to 20	90,000 gr.
21 x 62	1.5	14 to 28	108,000 gr.
24 x 72	1.5	20 to 40	180,000 gr.
30 x 72	2	30 to 60	270,000 gr.
36 x 72	2	40 to 70	360,000 gr.

\*\* Assumes 100% chloride.