

FILTER HOUSINGS



JUMBO STAINLESS STEEL FILTER HOUSINGS

SWT's **Jumbo Stainless Steel Filter Housings** are designed for food industry and high temperature applications with flow rates up to 30 gpm. Available for 10 or 20 inch Big Blue® filter cartridges, these high flow housings feature 304 stainless steel construction with food grade EPDM seals, 1 inch FNPT connections, and 1/4 inch NPT drain port.



FEATURES

- Eliminates risk of leaks and failures associated with plastic filter housings
- Solid metal construction in premium grade AISI 304 stainless steel
- Food-grade EPDM seals are standard (Viton seals are optional)
- Suitable for use with potable water and food products
- Accepts standard cartridges: 4-1/2 inch OD x 10 or 20 inch nominal length
- Spring-loaded seal plate in sump assures sealing with variable-length cartridges
- Installation kit includes mounting bracket and ring nut disassembly tool
- Sump features a 1/4 inch NPT drain plug

ADDITIONAL INFORMATION

Pressure: 150 psi (1.03 MPa) maximum

Temperature: 210°F (99°C) maximum

Cartridge Type: Double open ended style

Extras: Viton seals

Part Number	Cartridges		Flow Rate**		Connection Size		Dimensions	
	Length* Inches	Diameter Inches	GPM	LPM	Pipe NPT Inches	Drain NPT Inches	Height Inches	OD Inches
YH22501BB-S	10	4-1/2	15	56	1	1/4	15	5
YH22502BB-S	20	4-1/2	30	113	1	1/4	25	5

* Equivalent lengths accepted: 10 inch = (9.75 to 10 inch); 20 inch = (19.5 to 20 inch)

** Flow rates are for guidelines only. Actual flow rates are based on fluid, viscosity, cartridge type, micron ratings, and other factors.

Big Blue® is a registered trademark of Pentair Residential Filtration, LLC.